

## INTERIOR / EXTERIOR LIGHTS FIREFLY FLOOD



FIREFLY all new solid 316L Polished Stainless steel construction throughout.

Bracket mounted spreader light suitable for lighting deck and engine spaces around the yacht.

Flush mounted spreader light suitable for lighting any area around the yacht.

Surface mount spreader light suitable for lighting any areas around the yacht.

New Hydro Block Technology.

- 2-Year Warranty

SPECIFICATION	FIREFLY SPREADER LIGHTS		
	FF-B	FF-R	FF-S
Mounting Type	Bracket	Recessed	Surface
Hole cut out size			
Fixture Lumens	1000lm in cool white		
Max Wattage	14Watts max power consumption		
Typical Life Expectancy	50,000 Hours		
Voltage	9 - 32v		
Power Draw	Supply current max 1.2Amps at 12V to 600mA at 24V		
Protection	Over / Under Voltage, Over Current, Reverse Polarity protection, Active thermal protection. Hydro block technology		
Fixture Profile			
Fixture Diameter			
Lens Type	Toughened optical glass lens		
Fixture Material	All 316L Stainless steel		
Beam Angle	Two beam patterns available Flood or focused spot		
Warranty	2 Year		
Type Approval			
Available Colours	Warm white, Cool white & Blue.		
Suitable Use	Bow Lights, Spreader lights, Utility Lights or Engine/Locker spaces. For use above the water line.		
Driver Type	Integral		
Total weight			
Attached cable length	Integrated over moulded 2 core cable 200mm tail.		
Included in box	In-line fuse holder & rated fuse, Gel connector, Inline Crimps, Heat shrink, Fixing Screws, Template and installation instructions		
<b>ACCESSORIES</b>	<b>(OPTIONAL)</b>		
Junction Box	4 Way IP68 Wiring Junction Box		
I.Y.S Lighting Control	Control via MFD screen or mobile device		



